



Fasco Gulf Building Materials

P.O.Box-16135, Dubai, UAE.

PHONE: 009714-2676612

FAX: 009714-2676604

EMAIL: FASCO@EIM.AE



Company Profile:

We have pleasure in introducing FASCO GULF Building Materials based in Dubai, UAE. Since 1994 Fasco is a sales & service oriented and professionally managed company specialized in dealing with General hardware / Tools / Safety shoes / Safety Gloves , Specialty Fastners in all Grades & Forms.

Which includes Aluminium / Brass / Copper / Steel / Stainless Steel / High Tensile / Plastic Fastners in Polyester / Polypropylene / PVC.

Furthermore, we also cater to the needs of Industrial Fastners for Oil & Gas Installation in different ASTM – BS – DIN – ISO Standards with accredited Test Reports.

Fastener Grades :

Standard Steel Grades: 4.6/6.8/8.8/10.9/12.9

Stainless Steel Grades: A2/304 / A4/316 / L - Specials.

Hex Head Bolt as per ISO-898 - 4014 - 4017

BS 3692 Gr.8 / 8.8

BS 4395 I Gr.8.8 / Gr. 10

BS 14399 3 Gr.10 / 10.9

ASTM A 307 Grade

ASTM A 325 Inch / Metric Type 1 & III

ASTM A 490 Heavy Hex Bolt

ASTM A 563 Heavy Hex Nut

ASTM A 193 Grade B7 Stud

ASTM A 194 Grade 2H Heavy Hex Nut

ASTM F 436 Washers

Shear Welding Studs / Arc Welding Studs


In different material coatings, Galvanised / Zinc / Hot Dipped Galvanised / Sheradized / PTFE & Specials.


Complete range of Plastic Fasteners, in PVC - Polymers etc.




Blind Rivets & Self Tapping / Self Drilling Screws.



DIN	ISO		DESCRIPTION
916	4029		Hexagon socket set screws with cup point
917			Hexagon cap nuts
921			Slotted pan head screws with large head
923			Slotted pan head screws with shoulder, dog point
928			Square weld nuts
929			Hexagon weld nuts
931	4014		Hexagon head bolts
933	4017		Hexagon head screws
933 SZ			Slotted hexagon head screws
934	4032		Hexagon nuts
934	8673		Hexagon nuts with metric fine pitch
934			Hexagon nuts with left hand thread
935	7035		Hexagon slotted and castle nuts
937	7038		Hexagon thin slotted and half castle nuts
938			Studs, thread end = 1xd
939			Studs, thread end = 1,25xd
963	2009		Slotted countersunk head screws
964	2010		Slotted raised countersunk (oval) head screws
965 H	7046		Cross recessed countersunk (flat) head scr. Phill.
965 Z	7046		Cross recessed countersunk (flat) head screw Pozi.
966 H/Z	7047		Cross recess. Counters. (oval) head screws Phill./Pozi.
976 - 1			Threaded rods
976 - 1			Threaded pins, type B
980	7042		Prevailing torque type hexagon nuts full metal
982	7040		Prevailing torque hex. nuts with non-metal insert, high type
985	10511		Prevailing torque type hexagon nuts w. non-metalic ins., low type
986			Prevailing torque type hexagon domed cap nut. w. non-metalic ins.
988			Shim rings
1052			Washers for wood constructions
1440	8738		Plain washers for clevis pins
1471	8744		Grooved pins, full length taper grooved
1472	8745		Grooved pins, half length taper grooved


DIN	ISO		DESCRIPTION
1473	8740		Grooved pins, full length parallel grooved, with chamfer
1474	8141		Grooved pins, half length reverse taper gooved
1475	8142		Grooved pins, third length reverse taper gooved
1476	8746		Grooved pins, round head
1481	8752		Spring type straight pins, slotted
1587			Heavy type hexagon domed cap nuts
1804			Slotted round nut for hook spanner
2093			Disc springs
2510			Hexagon nuts for bolts with reduced shanks
3017			Hose clamp, with worm gear drive, type A
3570			U-Bolts, type A, without hexagon nuts
	UNI 5587		Hexagon nuts, high type, italian norm
6319			Spherical washers, type C / Conical washers, type D
6330			Hexagon nuts 1,5 d, type B
6331			Hexagon nuts 1,5 d with collar
6334			Long hexagon nuts
6796			Conical spring washers for bolted connections
6797			Toothed lock washers, form A and J
6798			Serrated lock washers, form A and J
6799			Retaining washers for shafts
6885			Parallel keys, type A
6900			Screw assemblies, metric thread
6901			Tapping screw assemblies
6912			Hex. socket head scr. w. centre hole, low profile
6921			Hexagon head screws w. flange
7337			Blind rivets, type A
7343	8750		Spiral pins, medium duty
7349			Springs pins, slotte, light type
7500	M + C		Washers for bolts with heavy type spring pins form M and C
7504	K+N+P		Self drilling screws, form K, N and P
7516			Thread cutting screws
7967			Self locking counter nuts

DIN	ISO		DESCRIPTION
7971	1481		Pan head tapping screws with slot, type C
7972	1482		Countersunk head tapping screws, with slot, type C
7973	1483		Raised Countersunk head tapping screws with slot, type C
7976	1479		Hexagon tapping screws, type C
7980			Spring lock washers for screws with cylindrical heads
7981 H/Z	7049		Pan head tapping screws with cross recessed, type C and F
7982 H/Z	7050		Countersunk flat head tapping scr. w. cross recess, type C and F
7983 H/Z	7051		Raised Countersunk head tapping scr. w. cross rec., type C and F
7984			Hex. socket head cap screws with low head
7985 H/Z	7045		Cross recessed raised pan head screws
7989			Washers f. steel constructions
7991	10642		Hexagon socket countersunk head screws
7993			Snap rings for shafts, type A
7995 H/Z			Cross recessed raised counters. head wood screws
7996 H/Z			Cross recessed round head wood screws
7997 H/Z			Cross recessed countersunk head wood screws
9021	7093		Washers w. outside diameter ≈ 3x nominal thr. diam.
11024			Spring cotter of bolt
25201			Selbsthemmende Sicherungsscheiben
WS	EN ISO		DESCRIPTION
9100			Chipboard screws with countersunk head, full thread, pozidrive
9105			Chipboard screws with countersunk head, part thread, pozidrive
9110			Panhead chipboard screws, full thread, pozidrive
9112			Panhead chipboard screws, with six lobe drive, full thread
9115			Panhead chipboard screws, with part thread, pozidrive
9117			Panhead chipboard screws, with six lobe drive, part thread
9120			Raised counters. chipboard screw full thread, pozidrive
9122			Raised counters. chipboard scr. with six lobe drive, full thread
9125			Raised counters. chipboard screw, part thread, pozidrive
9127			Raised countersunk chipboard scr. with six lobe drive, part thread
9130			Chipboard screws with counters. head, six lobe drive, full thread
9135			Chipboard screws with counters. head, six lobe drive., part thread

WS	ISO		DESCRIPTION
9145			Counters. chipb. screws w. six lobe drive, part threaded self drill, 6 ribs
9150			Teak deck screws, pozi drive
9155			Teak deck screws, six lobe drive
9160			Self threading screws for plastic materials
9165			Self drilling scr. simil. DIN 7504 K w. attached EPDM sealing washers
9166			Self drilling screws similar DIN 7504 N with six lobe drive
9167			Self drilling screws similar DIN 7504 P with six lobe drive
9170 - 9178			Wood scr. w. EPDM - washers Z + six drive, A2+ A2 copper-plated
9180 - 9198			Self tapping screws
9200			Tapping screws with head DIN 912
9209			Dowel screws without centre
9210			Dowel screws with centre
9211			Dowel screws with hexagon
9213			Dowel screws with six lobe drive
9215 - 9216			Dowel screws with hexagon and assembled nuts and washers
9218			EPDM-sealings for dowel screws
9220			Pan head tapping screws with mounted polyamid washer
9230			Slotted hexagon tapping screws with mount. poly. washer with slot
9231			Slotted hexagon tapping screws
9235			Self tapping screws with caphead similar DIN 7981
9236			Cover caps for self tapping screws
9240			Plain washers
9245 - 9248			Washers to French Norm NFE 25-514
9250			Locking washers "S"
9255			Finishing washers
9260			EPDM sealing washers
9265 - 9269			Serrated locking washers, type M/S/B/Z/K
9270			Self tapping inserts (ENSAT)
9280			Rampa insert bushings, type B
9290			Round coupler nuts
9300			Hexagon coupler nuts
9305			Shear off nuts

WS	ISO	DESCRIPTION
9310		Insert - press nuts
9312		Drive-in nuts
9314		Countersunk blind rivet nuts, low head
9315		Flat head blind rivet nuts
9316		Countersunk blind rivet nuts
9317		Flat headed blind rivet nuts, hexagonal shank
9318		Countersunk blind rivet nuts, low head, hexagonal shank
9320		Weld on nuts, type A, B and C
7380		Hexagon socket button head screws
9330		Slotted mushroom head screws
9332		Screws for fence building similar ISO 7380 with hexagon socket
9335		Hexagon socket button head screws with flange
9340		Slotted sleeve nuts
9345		Hexagon flange nuts with serration, similar DIN 6923
9400 - 9420		Hammer head screws for type 50/30, 40/22, 38/17, 28/15, 20/12
9440		U - bolts
9450		Cheese head screws, combi cross slot, type H/SZ
9460		Pan head screws six lobe drive, similar DIN 7985
9465		Hexagon socket button head scr. w. six lobe drive similar ISO 7380
9470		Counters. head screws, six lobe drive, similar DIN 7991
9475		Counters. head screws, six lobe drive, similar DIN 965
9477		Pan head tapping screws with six lobe drive, sim 7981
9478		Counters. flat head tapping screws with six lobe drive, sim 7982
9479		Raised counters head tapping screws w. six lobe drive, sim 7983
9480		Security screws similar to ISO 7380, six lobe drive & pin
9482		Security screws similar to DIN 7991, six lobe drive & pin
9485		Security screws to DIN 7981, six lobe drive & pin
9486		Security screws sim. to DIN 7982, six lobe drive & pin
9488		Bits for security screws with six lobe drive and pin
9489		L-keys with six lobe drive and pin
9495		Star inserts for six lobe drive
9500		Washers (Polyamid) DIN 125, type A

WS	ISO	DESCRIPTION
9510		Washers (Polyamid) DIN 1921
9580		Lifting eye screws, casted
9582		Lifting eye nuts, casted
9800		Decking scr. w. lower countersunk head, six lobe drive, thread end SB
9810		Washer head screws, six lobe drive, thread end SB
9820		Decking screws, milling ribs, lower countersunk head, thread end SB
9850		Dowel screws for concrete, hard metal points, technical approval
9851		Concrete screws w. hexagon head, hard met. points, technical approval
9350		VA-A/Anchor VA Stud
9360		VA-P/Chemical anchor capsule
9365		Chemical anchor cartridge VM-K
9370		Wedge anchor type "B"
9372		Wedge anchor type "Z"
9380		Drop - in anchor type "E"
9390		Universal plug type "UD"
FITTINGS		DESCRIPTION
DIN 2982 A		Weld nipples
DIN 2982 R		Double nipples
DIN 2986 G		Socket full
DIN 2986 H		Socket half
WS 9601		Elbow 90° int./int. thread
WS 9603		Elbow 45° int./int. thread
WS 9607		“T”, internal thread
WS 9611		Union, flat sealing, int. thread
WS 9612		Union, conical sealing, int. thread
WS 9625		Hexagon reducing bushings
WS 9626		Hexagon screws caps
WS 9630		Hexagon screws plugs
WS 9635		Reducing sockets
WS 9637		Hexagon hose nipples
WS 9640		Hexagon double nipples
WS 9641		Hex. reducing double nipples




k max.	1,4	1,7	2,0	2,8	3,5	4,0	5,3	6,4	7,5	8,8	10,0	11,5	12,5
s	4	5	5,5	7	8	10	13	17	19	22	24	27	30
e	4,32	5,45	6,01	7,66	8,79	11,05	14,38	18,90	21,10	24,49	26,75	30,14	33,53
●	4	5	5,5	7	8	10	13	17	19	22	24	27	30
Length / Ø	M2	M2,5	M3	M4	M5	M6	M8	M10	M12	M14	M16	M18	M20
3	▲ ●	▲ ●											
4	▲ ●	▲ ●											
5	▲ ●	▲ ●											
6	▲ ●	▲ ●	▲ ●	▲ ●									
8	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●						
10	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●					
12	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●					
14	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●					
16	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●				
18	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●				
20	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●		
22			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●		
25			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	
30			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
35			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
40			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
45			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
50			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
55				▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
60				▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
65				▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
70				▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
75					▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
80					▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
85						▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
90						▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
SU	1000	1000	1000 ≥ 25 500	1000 ≥ 25 500	500 ≥ 45 200 ≥ 70 100	500 ≥ 14 200 ≥ 45 100	200 ≥ 25 100 ≥ 85 50	100 ≥ 50 50	100 ≥ 50 50	25	25	25	25

■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.
Example item no. 933-2-8X40 DIN 933 - A2 - M8 - l = 40mm

Hexagon head screws

full thread




k max.	4,0	5,3	6,4	7,5	8,8	10,0	11,5	12,5
s	10	13	17	19	22	24	27	30
e	11,05	14,38	18,90	21,10	24,49	26,75	30,14	33,53
●	10	13	17	19	22	24	27	30
Length /Ø	M6	M8	M10	M12	M14	M16	M18	M20
95	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
100	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
110	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
120	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
130		▲●	▲●	▲●	▲●	▲●	▲●	▲●
140		▲●	▲●	▲●	▲●	▲●	▲●	▲●
150		▲●	▲●	▲●	▲●	▲●	▲●	▲●
160		▲●	▲●	▲●		▲●		▲●
170		▲●	▲●	▲●		▲●		▲●
180		▲●	▲●	▲●		▲●		▲●
190		▲●	▲●	▲●		▲●		▲●
200		▲●	▲●	▲●		▲●		▲●
250				▲●		▲●		▲●
SU	100	100 ≥ 85 50 ≥ 160 25	50 ≥ 160 25	50 ≥ 100 25	25 ≥ 150 10	25 ≥ 150 10	25 ≥ 130 10	25 ≥ 130 10

■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.
Example item no. 933-2-8X40 DIN 933 - A2 - M8 - l = 40mm

Hexagon head screws


with shank



b≤125	16	18	22	26	30	34	38	42	46	50	54	60	66	72	78
b>125	22	24	28	32	36	40	44	48	52	56	60	66	72	78	84
s	8	10	13	17	19	22	24	27	30	32	36	41	46	50	55
k min.	3,35	3,85	5,15	6,22	7,32	8,62	9,82	11,28	12,28	13,78	14,78	16,65	18,28	20,58	22,08
e	8,79	11,05	14,38	18,90	21,10	24,49	26,75	30,14	33,53	35,72	39,98	45,2	50,85	55,37	60,79
●	8	10	13	17	19	22	24	27	30	32	36	41	46	50	55
Length / Ø	M5	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24	M27	M30	M33	M36
25	▲●	▲●													
30	▲●	▲●	▲●												
35	▲●	▲●	▲●	▲●											
40	▲●	▲●	▲●	▲●	▲●										
45	▲●	▲●	▲●	▲●	▲●		▲●								
50	▲●	▲●	▲●	▲●	▲●	▲●	▲●								
55	▲●	▲●	▲●	▲●	▲●	▲●	▲●								
60	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●						
65	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●						
70	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●				
75	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●				
80	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●		
85	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	
90	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
95	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
100	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
110		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
120		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
130		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
140		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
150		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
160		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
170		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
SU	500 ≥ 45 200	200 ≥ 45 100	200 ≥ 45 50 ≥ 180 25	100 ≥ 50 50 ≥ 100 25 ≥ 160 10	50 ≥ 100 25 ≥ 160 10	50 ≥ 100 25 ≥ 150 10	25 ≥ 130 10	25 ≥ 130 10	25 ≥ 130 10	25 ≥ 130 10	20 ≥ 80 10	10 ≥ 160 5	10 ≥ 160 5	10 ≥ 130 5	5

■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.

Example item no. 931-2-8X40 DIN 931 - A2 - M8 - l = 40mm




b≤125	18	22	26	30	34	38	42	46	50	54	60	66	72	78
b>125	24	28	32	36	40	44	48	52	56	60	66	72	78	84
s	10	13	17	19	22	24	27	30	32	36	41	46	50	55
k min.	3,85	5,15	6,22	7,32	8,62	9,82	11,28	12,28	13,78	14,78	16,65	18,28	20,58	22,08
e	11,05	14,38	18,90	21,10	24,49	26,75	30,14	33,53	35,72	39,98	45,2	50,85	55,37	60,79
●	10	13	17	19	22	24	27	30	32	36	41	46	50	55
Length /Ø	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24	M27	M30	M33	M36
180	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
190	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
200	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
210		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
220		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
230		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
240		▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
250			▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
260			▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
270			▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
280			▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
290			▲●	▲●		▲●		▲●		▲●	▲●	▲●		
300			▲●	▲●		▲●		▲●		▲●	▲●	▲●		
320			▲●	▲●		▲●		▲●		▲●	▲●			
340			▲●	▲●		▲●		▲●		▲●	▲●			
360			▲●	▲●		▲●		▲●		▲●				
380			▲●	▲●		▲●		▲●		▲●				
400			▲●	▲●		▲●		▲●		▲●				
420			▲●	▲●		▲●		▲●		▲●				
440			▲●	▲●		▲●		▲●		▲●				
460			▲●	▲●		▲●		▲●		▲●				
480			▲●	▲●		▲●		▲●		▲●				
500			▲●	▲●		▲●		▲●		▲●				
SU	100	25	25 ≥ 210 10	10	10	10	10	10	10	10 ≥ 200 5	5	5	5	5

■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.
Example item no. 931-2-8X40 DIN 931 - A2 - M8 - l = 40mm

DIN 934 - sim. ISO 4032

Hexagon nuts



d	m min.	s	e	●
M1,4	0,95	3	3,28	3
M1,6	1,05	3,2	3,41	3,2
M1,7	1,15	3,5	3,82	3,5
M2	1,35	4	4,32	4
M2,3	1,55	4,5	4,88	4,5
M2,5	1,75	5	5,45	5
M2,6	1,75	5	5,45	5
M3	2,15	5,5	6,01	5,5
M3,5	2,55	6	6,58	6
M4	2,90	7	7,66	7
M5	3,70	8	8,79	8
M6	4,70	10	11,05	10
M7	5,20	11	12,12	11
M8	6,14	13	14,38	13
M10	7,64	17	18,90	17
M12	9,64	19	21,10	19
M14	10,30	22	24,49	22
M16	12,30	24	26,75	24
M18	14,30	27	29,56	27
M20	14,90	30	32,95	30
M22	16,90	32	35,03	32
M24	17,70	36	39,55	36
M27	20,70	41	45,20	41
M30	22,70	46	50,85	46
M33	24,70	50	55,37	50
M36	27,40	55	60,79	55
M39	29,40	60	66,44	60
M42	32,40	65	71,30	65
M45	34,40	70	76,95	70
M48	36,40	75	82,60	75
M52	40,40	80	88,25	80
M60	46,40	90	99,21	90
M64	49,10	95	104,86	95

Grade	SU
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	500
▲ ●	500
▲ ●	200
▲ ●	100
▲ ●	100
▲ ●	50
▲ ●	50
▲ ●	50
▲ ●	25
▲ ●	25
▲ ●	25
▲ ●	10
▲ ●	10
▲ ●	10
▲ ●	5
▲ ●	5
▲ ●	1
▲ ●	1


■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.
Example item no. 934-2-10 DIN 934 - A2 - M10

Hexagon nuts DIN 934 with fine pitch thread, left hand thread as well as UNC/UNF, with AD2000-W2 and made of special materials can be found on the following pages. Please note that nuts according to DIN 934 up to M24 will be delivered as standard in A2-70 and A4-80. The material A2-80 can be found on one of the following pages in this catalogue. Hexagon nuts with changed wrench sizes according to ISO 4032 can be found on the following pages.

DIN 127 A

Spring lock washers

type A, positive pattern



nominal size	for	d1	d2	h min.	s	b
3	M3	3,1	6,2	1,9	0,8	1,3
3,5	M3,5	3,6	6,7	1,9	0,8	1,3
4	M4	4,1	7,6	2,1	0,9	1,5
5	M5	5,1	9,2	2,7	1,2	1,8
6	M6	6,1	11,8	3,6	1,6	2,5
7	M7	7,1	12,8	3,6	1,6	2,5
8	M8	8,1	14,8	4,6	2,0	3,0
10	M10	10,2	18,1	5,0	2,2	3,5
12	M12	12,2	21,1	5,8	2,5	4,0
14	M14	14,2	24,1	6,8	3,0	4,5
16	M16	16,2	27,4	7,8	3,5	5,0
20	M20	20,2	33,6	8,8	4,0	6,0
24	M24	24,5	40,0	11,0	5,0	7,0
27	M27	27,5	43,0	11,0	5,0	7,0
30	M30	30,5	48,2	13,6	6,0	8,0

Grade	SU
▲ FS	1000
▲ FS	1000
▲ FS	1000
▲ FS	1000
▲ FS	1000
▲ FS	1000
▲ FS	500
▲ FS	500
▲ FS	500
▲ FS	500
▲ FS	100
▲ FS	100
▲ FS	50
▲ FS	50



■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.
Example item no. 127-2-8A DIN 127 - A2 - nominal size 8mm - form A - FS = spring steel

The DIN 127 has been withdrawn and was not replaced. The product is still available from stock. Material A2 and A4 have a reduced spring resistance in comparison to the material 1.4310 (spring steel). Spring lock washers for cheese head screws can be found as DIN 7980 in this catalogue.

DIN 125 A - sim. ISO 7089

Plain washers

type A without chamfer



d1	for	d2	h
1,7	M1,6	4,0	0,3
1,8	M1,7	4,5	0,3
2,2	M2	5,0	0,3
2,5	M2,3	6,0	0,5
2,7	M2,5	6,0	0,5
2,8	M2,6	7,0	0,5
3,2	M3	7,0	0,5
3,7	M3,5	8,0	0,5
4,3	M4	9,0	0,8
5,3	M5	10,0	1,0
6,4	M6	12,0	1,6
7,4	M7	14,0	1,6
8,4	M8	16,0	1,6
10,5	M10	20,0	2,0
13,0	M12	24,0	2,5
15,0	M14	28,0	2,5
17,0	M16	30,0	3,0
19,0	M18	34,0	3,0
21,0	M20	37,0	3,0
23,0	M22	39,0	3,0
25,0	M24	44,0	4,0
28,0	M27	50,0	4,0
31,0	M30	56,0	4,0
34,0	M33	60,0	5,0
37,0	M36	66,0	5,0
40,0	M39	72,0	6,0
43,0	M42	78,0	7,0
46,0	M45	85,0	7,0
50,0	M48	92,0	8,0
52,0	M50	92,0	8,0
54,0	M52	98,0	8,0

Grade	SU
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	500
▲●	500
▲●	200
▲●	200
▲●	200
▲●	200
▲●	100
▲●	100
▲●	50
▲●	25
▲●	25
▲●	10
▲●	10
▲●	10
▲●	10
▲●	10
▲●	10



■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.

Example item no. 125-2-8,4 DIN 125 - A2 - Ø 8,4mm - form A

Plain washers with 200 HV ISO 7089 can be found on the following pages. Washers for hexagon socket head cap screws can be found as DIN 433 in this catalogue. Polyamid washers can be found as WS 9500, plain washers with an expanded contact surface can be found as DIN 9021 in this catalogue.

sim. ISO 7049 - **DIN 7981 Z**
Tapping screws

pan head with cross recess Z (Pozidrive), type C (with cone point)



dk	4,2	5,6	6,9	7,5	8,2	9,5	10,8	12,5
k min.	1,55	1,95	2,35	2,55	2,75	3,25	3,65	4,25
k max.	1,80	2,20	2,60	2,80	3,05	3,55	3,95	4,55
r max.	0,3	0,4	0,5	0,5	0,6	0,7	0,8	0,9
⊕	Z 1	Z 1	Z 2	Z 2	Z 2	Z 2	Z 3	Z 3
Length / Ø	ST2,2	ST2,9	ST3,5	ST3,9	ST4,2	ST4,8	ST5,5	ST6,3
6,5 (1/4")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	
9,5 (3/8")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	
13 (1/2")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
16 (5/8")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
19 (3/4")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
22 (7/8")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
25 (1")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
32 (1 1/4")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
38 (1 1/2")		▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
45 (1 3/4")			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
50 (2")			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
60 (2 3/8")			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
70 (2 3/4")				▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
80 (3 1/8")				▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
90 (3 1/2")					▲ ●	▲ ●	▲ ●	▲ ●
100 (4")						▲ ●	▲ ●	▲ ●
SU	1000	1000	1000 ≥ 32 500	1000 ≥ 32 500	1000 ≥ 32 500 ≥ 50 200	1000 ≥ 22 500 ≥ 32 200	500 ≥ 32 100	200 ≥ 32 100


■ A1 / ▲ A2 / ● A4 | SU: Sales units | All measurements in mm / inch | Other dimensions on request.
Example item no. 7981-2-4,2X38Z DIN 7981 - A2 - Ø 4,2mm - l = 38mm - pozidrive

Tapping screws with pan head DIN 7981 with cutting groove type SB are available on request. Tapping screws with pan head DIN 7981 with different coatings or head varnishing are available on request. Tapping screws with pan and cap head can be found as WS 9235, with polyamide-washer as WS 9220, with TX as WS 9477 and as security screw with TX+PIN at WS 9485 in this catalogue.

DIN 7982 H - sim. ISO 7050

Tapping screws

countersunk head with cross recess H (Phillips), type C (with cone point)




dk	4,3	5,5	6,8	7,5	8,1	9,5	10,8	12,4
k	1,3	1,7	2,1	2,3	2,5	3,0	3,4	3,8
⊕	P 1	P 1	P 2	P 2	P 2	P 2	P 3	P 3
Length / Ø	ST2,2	ST2,9	ST3,5	ST3,9	ST4,2	ST4,8	ST5,5	ST6,3
6,5 (1/4")	▲ ●	▲ ●	▲ ●	▲ ●				
9,5 (3/8")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●		
13 (1/2")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
16 (5/8")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
19 (3/4")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
22 (7/8")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
25 (1")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
32 (1 1/4")	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
38 (1 1/2")		▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
45 (1 3/4")			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
50 (2")			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
55 (2 1/8")			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
60 (2 3/8")			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
70 (2 3/4")			▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
80 (3 3/8")					▲ ●	▲ ●	▲ ●	▲ ●
90 (3 1/2")					▲ ●	▲ ●	▲ ●	▲ ●
100 (4")					▲ ●	▲ ●	▲ ●	▲ ●
120 (4 3/4")						▲ ●	▲ ●	▲ ●
SU	1000	1000	1000 ≥ 32 500	1000 ≥ 32 500	1000 ≥ 32 500 ≥ 50 200	1000 ≥ 22 500 ≥ 32 200	200 ≥ 32 100	200 ≥ 32 100

■ A1 / ▲ A2 / ● A4 | SU: Sales units | All measurements in mm / inch | Other dimensions on request.
Example item no. 7982-2-4,2X38 DIN 7982 - A2 - Ø 4,2mm - l = 38mm

Tapping screws with countersunk head DIN 7982 with cutting groove type SB are available on request. Tapping screws with countersunk head DIN 7982 with different coatings or head varnishing are available on request. Slotted tapping screws with countersunk head can be found as DIN 7972, with TX as WS 9478 and as security screw with TX+PIN as WS 9486 in this catalogue.

DIN 7337 type A - sim. ISO 15983

Blind rivets



d1	d2	clamp. range	l	e
3,0	6,5	1,0 - 3,0	6	0,8
3,0	6,5	3,0 - 5,0	8	0,8
3,0	6,5	5,0 - 7,0	10	0,8
3,0	6,5	7,0 - 9,0	12	0,8
3,0	6,5	8,0 - 12,0	16	0,8
3,2	6,5	1,0 - 3,0	6	0,8
3,2	6,5	3,0 - 5,0	8	0,8
3,2	6,5	5,0 - 7,0	10	0,8
3,2	6,5	7,0 - 9,0	12	0,8
3,2	6,5	9,0 - 12,0	14	6,5
3,2	6,5	9,0 - 12,0	16	0,8
4,0	8,0	1,0 - 2,5	6	1,0
4,0	8,0	2,5 - 4,5	8	1,0
4,0	8,0	4,5 - 6,5	10	1,0
4,0	8,0	6,5 - 8,5	12	1,0
4,0	8,0	12,0 - 16,0	14	1,0
4,0	8,0	8,5 - 12,0	16	1,0
4,0	8,0	11,5 - 14,0	18	1,0
4,0	8,0	12,0 - 16,0	20	1,0
4,0	8,0	12,0 - 16,0	25	1,0
4,8	9,5	2,0 - 4,0	8	1,1
4,8	9,5	4,0 - 6,0	10	1,1
4,8	9,5	6,0 - 8,0	12	1,1
4,8	9,5	8,0 - 11,0	16	1,1
4,8	9,5	10,0 - 13,0	18	1,1
4,8	9,5	11,0 - 15,0	20	1,1
5,0	9,5	2,0 - 4,0	8	1,1
5,0	9,5	4,0 - 6,0	10	1,1
5,0	9,5	6,0 - 8,0	12	1,1
5,0	9,5	8,0 - 11,0	16	1,1
5,0	9,5	10,0 - 13,0	18	1,1
5,0	9,5	11,0 - 15,0	20	1,1
5,0	9,5	15,0 - 20,0	25	1,1

[illegible]

■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.


Example item no. 7337-2-4X8 DIN 7337 - A2 - Ø 4mm - l = 8mm - *1 Tip depends on production - *2 breaking point

Blind rivets with countersunk head DIN 7337 B with different types and A4 are available on request. Blind rivet nuts in different forms can be found as WS 9314 - WS 9318 in this catalogue. Solid rivets with half-round heads can be found as DIN 660, with countersunk head as DIN 661 in this catalogue.

DIN 976 - Page 1

Threaded rods


1m, 2m, 3m



Length /Ø	M2	M3	M4	M5	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24
1.000	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
2.000				▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
3.000				▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●	▲ ●
SU	1	1	1	1	1	1	1	1	1	1	1	1	1	1

■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.
Example item no. 976-2-10 DIN 976 - A2 - M10 - l = 1.000mm

LOCATION DIRECTION :



Location Direction : DAMASCUS ROAD DUBAI, Towards Sharjah Caterpillar RA.
Take 1st Turn Before Eppco Petrol Pump . (15th Street)
Take 1st Left Then Again 1st Left.
Come Forward 100 Metters Ahead.
1st Warehouse On Your Right Side (Yellow Colour)
(Opposite Emex Cargo)

24/7-365 Emergency Contact : 050 - 8585007